



## SPEEDFACE - 7



Face



Touch  
Screen



RFID



WiFi



LAN



USB



Access  
Control

## Facial Attendance and Access Control

### Storage Capacity

Face ID Capacity	50,000
Max Users	50,000
Card Capacity	50,000
Log Capacity	1,50,000



### Features

Speedy Recognition to avoid long queues

Access Control to secure your premises

Auto ON/OFF Energy saving light

Dust insulation with IP 65

Large 7 inch display with easy handling features

Dual Camera for live body sensing & observation

Strong Metal Build quality with Negligible Maintenance

# SpeedFace - 7

## Communication Interface

Communication	WiFi, TCP/IP, USB
---------------	-------------------

## Biometric

Push Data	YES
Remote firmware update	YES
FAR	0.001%
Accuracy ratio	99.27%
Processor	Dual Core ARM Cortex-A7 @900MHz
OS	Linux
Verification time	<=1 second
RF card options	Wiegand 26/34



Auto Focus



Low light Verification



Long Distance Verification

## Audio/Visual

LCD	7" IPS touch screen display
Shutter type	Electronic Rolling Shutter
Language	English

Software

Web & Cloud

## Access control

Wiegand out	YES
Relay	YES
Support	Rs232, Rs485, Wiegand26/34
Storage	512 MB RAM, 8GB ROM



Time Attendance



Access Control



Employee Self Service



Mobile App

## Power & Environment

Operating Temperature	0°C ~ 50°C
Working Humidity	10% ~ 90%
Power	12V DC / 2A
Dimension	232 x 122 x 38 mm

**Disclaimer :** Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by



[www.biomaxsecurity.com](http://www.biomaxsecurity.com)

Connect with us on



BiomaxOfficial



BioMax Security



biomaxsecurity



BioMax Access Control