



## FLG22

### Frameless Glass Door Lock



Finger



Mifare card



Remote



Access Control

## Frameless Glass Door Lock

### Storage Capacity

Finger Capacity	100
Card Capacity	100
Max User	100

### Features

High-Speed and Accurate Identification
Good adaptation for dry, moist and rough fingerprints
Fingerprint, Mifare Card, Password authentication
Supremely low Electric energy consumption
Metal body for durability
TN Colour Display for Convenience



## FLG22

### Biometric

Sensor type	Semi Conductor
FAR	0.001%
FRR	0.001%
Verification time	<=1 second
RFID	13.56MHz Mifare

### Audio/Visual

LCD	1.77" TN Colour Screen
Voice instruction	16-bit Hi-Fi voice
Language	English

### Power & Enviroment

Battery (Optional)	4 AA Battery (6V)
Emergency power supply	Powerbank (optional)
Operating Temperature	0°C ~ 50°C
Operating Humidity	20% - 80%RH
Power Cable	C type
Weight	1.42 kgs
Frame Thickness	10 mm-12 mm
Door Gap	4 mm-10 mm
Dimension (Main Lock)	188 x 83 x 79.5 mm
Dimension (Side Lock)	188 x 73 x 36.5 mm
Suitable	Frameless glass door,
	1 side framed glass door



Finger Print



Mifare card



Wireless Remote



Access Control



**Disclaimer :** Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by    

[www.biomaxsecurity.com](http://www.biomaxsecurity.com)

Connect with us on



BiomaxOfficial



BioMax Security



biomaxsecurity



BioMax Access Control