



# Multibio – 900

Visible Light Facial & Fingerprint Recognition



Face





MiFare

ר יייי





TCP/IP



Access Control

### Visible Light Indoor Facial Recognition

Storage Capacity	
Face Capacity	3,000
Finger Capacity	10,000
Card Capacity	3,000
Password Capacity	3,000
Log Capacity	2,00,000
Max User	3,000

#### Features

Speedy recognition to avoid long queue Large display with easy handling features Dual camera for live body sensing & observation Camera support low light and normal light Auto ON/OFF Energy saving light Access control to secure your premises Strong metal build quality with Negligible maintenance Multiple authentication modes like face,fingerprint & card



## Multibio - 900

#### Communication Interface

Communication	WiFi, TCP/IP, USB

#### **Biometric**

OS	Linux
Recognition distance	0.5-1 meters
Fingerprint Sensor	500 DPI Optical Sensor
FAR	0.00001%
FRR	0.001%
RF Card Options	13.56 Mhz Mifare

#### Audio/Visual

LCD Display	4.3" RGB Capacitive
	touch screen
Camera	2 MP Binocular camera
Voice instruction	16-Bit Hi-Fi Voice
Resolution	480*272 Pixel
IP Rating	IP65 Water and Dust resistance

#### Access Control

Wiegand	Out
Relay	Yes
Exit Reader	Wiegand Output, Remote
	Push Button, No Touch

#### Power & Enviroment

Operating Temperature	-20°C -+60 °C
Power	DC 12V / 2A
Dimension	185 x 90 x 23.8 mm
Working humidity	10% - 90%

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.



www.biomaxsecurity.com



Auto Focus



low light Verification



Long Distance Verification

Software Desktop, Web, Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

