



N-X990 + FC Most Versatile Model







RFID













Face

Finger

Battery (Optional)

WiFi

LAN

USB

GPRS (Optional

Access Control

Time Attendance and Access Control System

Storage Capacity

Face Capacity	1000
Finger Capacity	10,000
Card Capacity	10,000
Password	10,000
Max User	10,000
Log Capacity	1,50,000

Features

High-Speed and Accurate Fingerprint Identification Face, Fingerprint, Card, Password authentication


output relay for door open.

Good adaptation for dry, moist and rough fingerprints.

Supremely low Electric energy consumption.

Highly reliable and durable.

Comprehensive software development kit(SDK) is available for development and integration.




Communication Interface

WIFI, TCP/IP, USB, RS232/485 Communication

Biometric

D 1 D 1	V
Push Data	Yes
4G GPRS	Yes (Optional)
Sensor type	500 DPI
FAR	0.01%
FRR	0.001%
OS	Linux
Verification Time	<=1 second
Printer	Yes (Optional)
RF card options	125kHz EM (Standard) /
	13.56MHz Mifare (Optional)



Audio/Visual

LCD	3" TFT color screen
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

Software Desktop, Web, Cloud

Access control

Wiegand input/output	YES
Relay	YES
Support	RS485 Reader, Wiegand Reader,
	Remote, Push Button, No Touch



Time Attendance



Access Control



Employee Self Service



Mobile App

Power & Environment

Battery Backup	Yes (Optional)
Operating Temperature	0°c ~ 50°c
Power	12V DC / 2A
Dimension (L*H*W)	215 x 160 x 45 mm

Disclaimer: Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Connect with us on











