



# N-Z90 W Pro

MAXIMISING USERS TO LIMIT





Finger



RFID















Access Control

#### Multi-Bio Attendance and Access Control

## Storage Capacity

Face Capacity	2000
Finger Capacity	10,000
Card Capacity	10,000
Max User	10,000
Password	10,000
Log Capacity	1,50,000

#### **Features**

High-Speed and Accurate Fingerprint Identification

Face, Finger, Card, Password authentication


output relay for door open.

Good adaptation for dry, moist and rough fingerprints.

Supremely low Electric energy consumption.

Highly reliable and durable.

Comprehensive software development kit(SDK) is available for development and integration.



## Communication Interface

Communication WiFi, TCP/IP, RS232/485, USB

#### Biometric

Push Data	Yes
GPRS	Yes (Optional)
Printer	Yes (Optional)
Sensor type	500 DPI
FAR	0.01%
FRR	0.001%
OS	Linux
Processor	1GHz
Verification time	<=1 second
RF card options	125kHz EM (Standard) /
	13.56MHz Mifare (Optional)



Auto Focus



low light Verification



Long Distance Verification



Accepts Color Finger

## Audio/Visual

LCD	2.4" TFT Color Screen 480x272 pixel
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

Software Desktop, Web, Cloud

#### Access control

Wiegand input/output	YES
Relay	YES
Support Exit Reader	Wiegand Reader, RS485 Reader
	Push Button, Remote, No Touch



Time Attendance



Access Control



Employee Self Service



Mobile App

#### Power & Environment

Battery	Yes (Optional)
Operating Temperature	0°c ~ 50°c
Power	12V DC / 2A
Dimension	188 x 65 x 150 mm

**Disclaimer**: Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Connect with us on







BioMax Security





