

V-AX27

Poe Loaded, Ultimate



Finger



RFID



POE



LAN



Feather Touch Keypad



Access Control

Fingerprint Time Attendance and Access Control

Storage Capacity

Finger Capacity	3000
Card Capacity	3000
Max Users	3000
Password	3000
Log Capacity	50,000

Features

High-Speed and Accurate Fingerprint Identification

Fingerprint, Card, Password authentication

output relay for door open.

Good adaptation for dry, moist and rough fingerprints.

Supremely low Electric energy consumption.

Highly reliable and durable.

Comprehensive software development kit(SDK) is available for development and integration.



Communication Interface

Communication	TCP/IP, Rs485
---------------	---------------

Biometric

Keypad	Feather Touch Keypad
Sensor type	500 DPI
FAR	0.00001%
FRR	0.001%
POE	Standard IEEE802.3af
Verification time	<=1 second
RF card options	Mifare Card (Optional)



Accepts moist and rough Finger



Accepts Color & Mahendi Finger



Compact & lightweight design



Unaffected by High
Temperatures -20°C ~ 50°C

Audio/Visual

Display	128*64 OLED
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

Access control

Relay	YES
Support	V-R12, Wiegand Reader, Push Button, Remote, No Touch

Power & Enviroment

Operating Temperature	-20°C ~ 50°C
Power	DC 12V , 2Amp
Dimension	54(w)*170(h)*41(d)mm

Software

Desktop



Time Attendance



Access Control



Employee Self Service



Mobile App

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by



www.biomaxsecurity.com

Connect with us on



BiomaxOfficial



BioMax Security



biomaxsecurity



BioMax Access Control