



## SPEEDFACE 5SE Lite



Face



Live Body  
Detection



QR  
Code



Mifare



Wi-Fi



TCP/IP



Access  
Control

## Facial Attendance and Access Control

### Storage Capacity

Face Capacity	6,000
Card Capacity	6,000
QR Capacity	6,000
Max User	6,000
Log Capacity	2,00,000

### Features

5-inch capacitive touch screen.

DualCoreARM Cortex-A7 Processor.

Remotely Firmware Upgradation.

Live detection algorithm against color, Videos and 3D masks attack.

5-inch TN display all-sight LCD touch screen with 480\*854 resolution.

Ip42 Grade Highly finished slim device.

Highly reliable and durable.

Recognition speed 0.5 seconds.



# SpeedFace 5SE Lite

## Communication Interface

Communication	Wi-Fi, TCP/IP, USB
---------------	--------------------

## Biometric

Push Data	Yes
Remote firmware update	Yes
FAR	0.001%
Accuracy ratio	99.27%
Processor	Dual Core ARM Cortex-A7
OS	Linux
Verification time	<=1 second

## Audio/Visual

LCD	5.0" TN touch screen display
Shutter type	Electronic Rolling Shutter
Language	English

## Access control

Wiegand Out	Yes
Relay	Yes
Push button	Yes
Auxiliary	Input

## Power & Environment

Operating Temperature	-10°C ~ 50°C
Power	12V DC / 2A
Dimension	186 x 94 x 23 mm



Auto Focus



Autofill light



Long Distance Verification

Software

Web & Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

**Disclaimer :** Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by



[www.biomaxsecurity.com](http://www.biomaxsecurity.com)

Connect with us on



BiomaxOfficial



BioMax Security



biomaxsecurity



BioMax Access Control