

EM Lock with Feedback - EL 280GD FB



EM Lock with Feedback - EL 280GD FB

Technical Details

5 Wires Feedback EM Lock (NO-NC-COMM)	
Magnet	250 x 47 x 26 mm (L x W x H)
Armature Plate	180 x 38 x 11 mm (L x W x H)
Mounting Plate	250 x 25 x 6 mm (L x W x H)
Current	500ma
Power	12V
Holding Capacity	230 kg
Holding Force	600 lbs
Temperature	10°C – 55°C
Operand Humidity	0%-95% (Non-Considering)

Special Features

Green/Red indication for lock status
Design with no Mechanical Bolt
Voltage and current spike protection PCB
Superior Strength Aluminum Alloy, Solid Stainless Steel Bolt
Silent operation : no humming or buzzing
Finishing : Zinc
Suitable for : Wooden door, Glass Door, Aluminum door, Fireproof door
Optional Accessories : L Bracket, U Bracket, ZL Bracket

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by   

www.biomaxsecurity.com

Connect with us on



[BiomaxOfficial](#)

[BioMax Security](#)

[biomaxsecurity](#)

[BioMax Access Control](#)