



N-G4W Made to Dominate





Finger







WiFi



LAN









Access Control

Multi-Bio Attendance and Access Control System

Storage Capacity

Face Capacity	10,000
Finger Capacity	30,000
Card Capacity	10,000
Max Users	10,000
Log Capacity	2,00,000

Fetures

World-class Face Identification Technology

High-Speed and Accurate Fingerprint Identification

Face, Fingerprint, Card authentication

1 output relay for door open.

Self-Service Inquiry

Good adaptation for dry, moist and rough fingerprints.

Not necessary of bright lights during scans.

supremely low Electric energy consumption.

Comprehensive SDK is available for development & integration.



Communication Interface

Communication WIFI, TCP/IP, RS232/485, USB
--

Biometric

Push Data	Yes
4G GPRS	Yes (Optional)
GPS	Optional
Printer	Yes (Optional)
Sensor type	500 DPI
FAR	0.00001%
FRR	0.001%
Processor	1 GHz
OS	Linux
Verification time	<=1 second
RF card options	125kHz EM (Standard) /
	13.56MHz Mifare (Optional)



LCD	4.3" touch screen 480x272 pixel
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

Access control

Wiegand in & out	YES
Relay	YES
Support	RS485 Reader, Wiegand Reader,
	Remote, Push Button, No Touch

Power & Environment

Battery	Yes (Optional)
Operating Temperature	0°c ~ 50°c
Power	12V DC / 2A
Dimension (L*H*W)	195 x 150 x 100 mm





low light Verification



Long Distance Verification



Accepts Color Finger

Software Desktop, Web, Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

Disclaimer: Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.






(f) BiomaxOfficial



Connect with us on

BioMax Security



(in) BioMax Access Control