

# N-K30 Pro













Finger

**RFID** 

LAN

iB.

Access Control

## Time Attendance and Access Control

#### Storage Capacity

Finger Capacity	2000
Card Capacity	2000
Max User	2000
Password	2000
Log Capacity	1,50,000

#### **Features**

High-Speed and Accurate Fingerprint Identification
Fingerprint, Card, Password authentication
output relay for door open.



Good adaptation for dry, moist and rough fingerprints.

Supremely low Electric energy consumption.

Highly reliable and durable.

 $\label{lem:comprehensive} Comprehensive \ software \ development \ kit(SDK) \ is \ available \ for \ development \ and \ integration.$ 

## N-K30Pro

## Communication Interface

Communication TCP/IP, USB

#### Biometric

Push Data	Yes
Sensor type	500 DPI
FAR	0.00001%
FRR	0.001%
OS	Linux
Verification time	<=1 second
RF card options	Proximity / Mifare (Optional)

## Audio/Visual

Display	2.4" TFT LCD colour screen
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

#### Access control

Relay	Yes
Support	Remote, Push Button, No Touch
Standard Functions	Auto Status, Record Query
	T9 Input, 14 Digit User ID

#### Power & Environment

Operating Temperature	0°c ~ 50°c
Power	12V DC / 2A
Dimension (L*H*W)	180 x 130 x 45 mm



Accepts moist and rough Finger



Accepts Color & Mahendi Finger



Compact & lightweight design



Unaffected by High Temperatures 0° ~ 50°

Software Desktop, Web, Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

Disclaimer: Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Connect with us on















