



# N-Uface302 Pro Multi Bio









(Optional)











Finger

RFID

WiFi

LAN

USB

GPRS/GPS (Optional)

Access Control

## Multi-Bio Attendance and Access Control

# Storage Capacity

Face Capacity	3000
Finger Capacity	10,000
Card Capacity	3000
Max User	3000
Log Capacity	2,00,000

#### **Features**

High-Speed and Accurate Face Identification

Good adaptation for dry, moist and rough fingerprints.

Output relay for door open.

Face, Fingerprint, Card, Password authentication

Supremely low Electric energy consumption.

Highly reliable and durable.

Comprehensive SDK is available for development and integration.



# N-Uface302

#### Communication Interface

Communication TCP/IP, Wi-Fi, RS485, USB

#### Biometric

Diometrio	
Push Data	Yes
4G GPRS / GPS	Yes (Optional)
Sensor type	500 DPI
FAR	0.01%
FRR	0.001%
Processor	1 GHz
OS	Linux
Verification time	<= 1 second
RF card options	Proximity / Mifare (Optional)

## Audio/Visual

Display	2.8" TFT LCD color screen
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

#### Access control

Wiegand	Input / Output
Relay	Yes
Standard Functions	Anti-passback, Auto Status,
	Record Query, T9 Input, 14 Digit User ID
Support	N-FR12, KR26E, Remote,
	Push Button, No Touch

#### Power & Environment

Battery	Yes (Optional)
Operating Temperature	0°c ~ 50°c
Power	12V DC / 2A
Dimension (L*H*W)	175 x 120 x 95 mm



Auto Focus



low light Verification



Long Distance Verification



Accepts Color Finger

Software Desktop, Web, Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

Connect with us on

**Disclaimer**: Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.









