



N-X990 Most Versatile Model







Battery (Optional)











PRS

Access Control

Time Attendance and Access Control System

Storage Capacity

Finger Capacity	10,000
Card Capacity	10,000
Max User	10,000
Password	10,000
Log Capacity	1,50,000



Features

High-Speed and Accurate Fingerprint Identification
Fingerprint, Card, Password authentication
output relay for door open.

Good adaptation for dry, moist and rough fingerprints.

Supremely low Electric energy consumption.

Highly reliable and durable.

Comprehensive software development kit(SDK) is available for development and integration.

Communication Interface

Biometric

Push Data	Yes
4G GPRS	Yes (Optional)
Sensor type	500 DPI
FAR	0.00001%
FRR	0.001%
OS	Linux
Verification Time	<=1 second
Printer	Yes (Optional)
RF card options	Proximity / Mifare (Optional)

Audio/Visual

Display	3.2" TFT LCD color screen
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

Access control

Wiegand	Input / Output
Relay	Yes
Standard Functions	Anti-passback, Auto Status,
	Record Query, T9 Input, 14 Digit User ID
Support	N-FR12, KR26E, Remote,
	Push Button, No Touch

Power & Environment

Battery Backup	Yes (Optional)
Operating Temperature	0°c ~ 50°c
Power	12V DC / 2A
Dimension (L*H*W)	215 x 160 x 45 mm



Accepts moist and rough Finger



Accepts Color & Mahendi Finger



WiFi, TCP/IP, RS232/485, USB



Unaffected by High Temperatures 0° ~ 50°

Software

Desktop, Web, Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

Disclaimer: Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Connect with us on







BioMax Security









